



1. Material:

Insulator: PBT+30%G.F UL 94V-0
 Contact: Brass
 Shell: Spcc

2. Mechanical:

Mating: 35N max.
 Withdrawal Force: 10N min.
 Dural jifty: 1500 cycles min.

3. Electrical:

Current—max [amps]: 1.5A
 Voltage—max [volts]: 30V
 Withstanding Voltage: 750V AC.
 Contact Resistance [ohms]: 30mΩ max.
 Insulation Resistance [ohms]: 1000MΩ min.

4. Plating:

Contacts: Gold And Tin Over Nickel Plated.
 Shell: Nickel Over all Plating

5. Environmental:

Temperature Range: -55°C to +85°C

TOLERANCE			SELECT		TITLE:	
DN	TOL	1	2	3	SAN HUNG ENTERPRISE CO., LTD	
XXXX	±	0.05	0.05	0.15	USB AM 90° DIP	
XX	±	0.10	0.15	0.25	P/N: YH-USB-AM02	
XX	±	0.15	0.25	0.50	CUSTOMER PART/NO.:	
X	±	0.25	0.50	1.00	SCALE UNIT REV DATE	
ANGLE	±	T			1:1 mm AO 2005-04-13	
DRAWING: SEE NOTE			DR: 王周中		APPD: 刘智能	